

MATERIAL SAFETY DATA SHEET



SECTION 1 -- CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

| PRODUCT NAME | Aquapel Premium Windshield Washer Fluid & De-Icer |
|--------------|---|
| | |
| PRODUCT CODE | 47105 |

ISSUE DATE 12/08/08

DISTRIBUTOR STREET ADDRESS

CITY, STATE, ZIP

Pittsburgh Glass Works Pittsburgh, PA 15272 www.aquapel.com

EMERGENCY TELEPHONE NUMBERS

Transportation: 1-800-424-9300* One PPG Place 6th Floor East * For spill, leak, fire or transport accident emergencies. Product Information: 1-800-774-5555

Medical Information: 1-866-359-5662

SECTION 2 -- COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS EXPOSURE LIMITS COMPONENT CAS No. OSHA PEL ACGIH TLV % by wt. NIOSH REL Methanol 67-56-1 35.0-200 ppm 200 ppm None 36.0 2.0-2.3 Propylene Glycol 57-55-6 None None None

SECTION 3 -- HAZARDS IDENTIFICATION

| Can cause eye and skin irritation. |
|------------------------------------|
| Harmful if swallowed |
| Irritating to respiratory tract. |
| Danger: Poison, Flammable |
| Cannot be made non-poisonous. |
| |
| |

| SKIN CONTACT | Prolonged or repeated contact without rinsing with water may cause irritation. |
|--------------------------|--|
| EYE CONTACT | Irritating to eyes; may cause severe and permanent damage. |
| INHALATION | May cause headaches, dizziness, nausea, incoordination, drowsiness, visual impairment and unconsciousness. |
| INGESTION | Can cause blindness. |
| POTENTIAL HEALTH EFFECTS | |

SECTION 4 -- FIRST AID MEASURES

| INGESTION | Do not give liquid if victim is unconscious or drowsy. Otherwise, give 1 or 2 glasses of water. Call doctor, hospital emergency room or poison control center for instructions to induce vomiting. When medical advice is not available, induce vomiting using syrup of ipecac according to directions. If ipecac not available, induce vomiting with finger or back of spoon by touching the back of the victim's throat. Get medical attention. |
|----------------------|---|
| INHALATION | If exposed to excessive levels of vapors, remove to fresh air. |
| EYE CONTACT | Immediately flush eye with plenty of cool, running water. Remove contact lenses if applicable, and continue flushing for at least 15 minutes, holding eyelids apart to ensure thorough rinsing of the entire eye. Speed is essential to minimize injury. Call a physician immediately. |
| SKIN CONTACT | Immediately flush skin with plenty of cool running water for at least 15 minutes. Wash with soap and water. If irritation develops or persists, get medical attention. Remove contaminated clothing and shoes; wash before reuse. |
| NOTE TO PHYSICIAN | |

SECTION 5 -- FIRE FIGHTING MEASURES

| FLASH POINT / METHOD | 90 deg F | FLAMMABLE LIMITS | LEL: 6.7% UEL: 36.5% |
|----------------------------------|---|-------------------------------|-------------------------|
| EXTINGUISHING MEDIA | Use of dry chemical, carbon of | dioxide, water spray, alcohol | foam |
| SPECIAL FIRE FIGHTING PROCEDURES | Use fog or spray to prevent flooding. Be prepared to use MSHA-NIOSH self-contained breathing apparatus and protective clothing. | | |
| FIRE AND EXPLOSION HAZARDS | Treat as a flammable liquid. dangerous fire hazard. | There is the chance of a mod | lerate explosion and/or |

SECTION 6 -- ACCIDENTAL RELEASE MEASURES

| RESPONSE | Eliminate all sources of ignition immediately. Mop up residue and rinse area thoroughly with |
|-------------|--|
| TO SPILLS | water. Contain run-off with absorbent materials such as sand or clay and diking. Transfer liquid and |
| I O OI ILLO | absorbent material in approved container. Flush and mop area with water allowing to air dry. Keep |
| | spill out of sewers and open bodies of water. |

SECTION 7 -- HANDLING AND STORAGE

| HANDLING PRECAUTIONS | Follow directions on label. Wash after handling and before eating. |
|-------------------------|---|
| STORAGE PRECAUTIONS | Store container upright. Tighten cap securely. Avoid heat, sparks, and flames. Protect container from physical damage. Keep away from children. |

SECTION 8 -- EXPOSURE CONTROLS / PERSONAL PROTECTION

| HYGIENIC PRACTICES | Avoid breathing vapors. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Follow directions on label. Do not store near food stuffs, water or feed. |
|----------------------|--|
| ENGINEERING CONTROLS | Use local ventilation to remove vapors at the source. |

PERSONAL PROTECTIVE EQUIPMENT

| | RESPIRATOR | Jse NIOSH approved respirator if exposure exceeds PEL or TLV limits. | | |
|---|-----------------------|---|--|--|
| Χ | GOGGLES / FACE SHIELD | nemical splash goggles required; also use face shield if exposure is severe | | |
| | APRON | Recommended; PVC, Neoprene or Vinyl acceptable | | |
| | GLOVES | Recommended; use impervious PVC or Neoprene with long gauntlet | | |
| | BOOTS | Recommended to protect shoes and feet when using product for floor cleaning | | |

SECTION 9 -- PHYSICAL AND CHEMICAL PROPERTIES

| APPEARANCE | Clear blue-green liquid | BOILING POINT | 148 deg F |
|---------------------|-------------------------|------------------|-----------|
| ODOR | Slight alcohol aroma | FREEZING POINT | -30 deg F |
| рН | 8.0 – 8.5 | VAPOR PRESSURE | 97 |
| SPECIFIC GRAVITY | 0.940 | VAPOR DENSITY | 1.11 |
| SOLUBILITY IN WATER | 100% | EVAPORATION RATE | 5.9 |
| | | | |

SECTION 10 -- STABILITY AND REACTIVITY

| CHEMICAL STABILITY | | STABLE | Χ | | UNSTABLE | |
|-------------------------------------|------------------|------------------|---------|----------------|-----------|--|
| CONDITIONS TO AVOID | Heat, sparks, fl | ames. No smoki | ng wh | nen using. | | |
| INCOMPATIBILITY | Strong oxidizing | agents such as n | itrates | or sulfuric ad | cid. | |
| HAZARDOUS PRODUCTS OF DECOMPOSITION | Burning may pro | oduce carbon mon | oxide | and formalde | ehyde. | |
| POLYMERIZATION | | WILL NOT OCC | UR | X | MAY OCCUR | |
| CONDITIONS TO AVOID | Not applicable | | | | | |

SECTION 11 -- TOXICOLOGICAL INFORMATION

CARCINOGENICITY

| | | THIS PRODUCT CONTAINS A KNOWN OR SUSPECTED CARCINOGEN |
|---|---|---|
| Х | (| THIS PRODUCT DOES NOT CONTAIN ANY KNOWN OR ANTICIPATED CARCINOGENS ACCORDING |
| | | TO THE CRITERIA OF THE NTP ANNUAL REPORT ON CARCINOGENS AND OSHA 29 CFR 1910, Z |

OTHER EFFECTS

| ACUTE | Not determined |
|---------|----------------|
| CHRONIC | Not determined |
| | |
| | |

MSDS

PRODUCT Aquapel Premium
Windshield Washer Fluid & De-Icer

Aquapel 47105 PAGE 4 OF 4

SECTION 12 -- ECOLOGICAL INFORMATION

| BIODEGRADABILITY | | CONSIDERED BIODEGRADABLE X NOT BIODEGRADABLE | | | | |
|------------------|--------|--|--|--|--|--|
| BOD / COD VALUE | Not es | stablished | | | | |
| ECOTOXICITY | No da | ta available | | | | |

SECTION 13 -- DISPOSAL CONSIDERATIONS

| WASTE DISPOSAL METHOD | Poison Disposal: Poison wastes are acutely hazardous. Improper disposal of excess poison, spray or mixture of rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA regional office for guidance. Container Disposal: Triple rinse. Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill, or incineration, or if allowed by state and local authorities by burning. If burned stay out of smoke. Do not reuse empty container (bottle, can, bucket). Wrap container and put in trash. Do not add this product to any irrigation system. | | | | | | | | |
|-----------------------|--|-----|---|--|------|----------|--|----|--|
| RCRA CLASSIFICATION | Non-hazardous | | | | | | | | |
| RECYCLE CONTAINER | | YES | X | | CODE | 2 - HDPE | | NO | |

SECTION 14 -- TRANSPORT INFORMATION

| DOT CLASSIFICATION | HAZARDOUS | NOT HAZARDOUS X | | | |
|--------------------------------|--|-----------------|--|--|--|
| DOT Proper Shipping Name | Methanol Solution | | | | |
| Hazard Class 3 | | | | | |
| Identification Number | UN 1230 | | | | |
| Packing Group | | | | | |
| Label/Placard Flammable Liquid | | | | | |
| RQ | Methanol 5000 lbs (2270 kg) | | | | |
| Exceptions | Consumer Commodity, ORM-D; Exempted by DOT for containers of 1 gallon or less. | | | | |

SECTION 15 -- REGULATORY INFORMATION

REGULATORY STATUS

| | EPA REGISTERED (UNDER FIFRA) | |
|---|------------------------------|-------------|
| | FDA REGULATED | |
| | KOSHER | |
| Χ | SARA TITLE III MATERIAL | Section 304 |
| | USDA AUTHORIZED | |
| | | |

SECTION 16 -- OTHER INFORMATION

NFPA CLASSIFICATION

| 1 | BLUE | HEALTH HAZARD |
|---|--------|----------------|
| 3 | RED | FLAMMABILITY |
| 0 | YELLOW | REACTIVITY |
| | WHITE | SPECIAL HAZARD |

Information contained in this MSDS refers only to the specific material designated and does not relate to any process or use involving other materials. This information is based on data believed to be reliable, and the Product is intended to be used in a manner that is customary and reasonably foreseeable. Since actual use and handling are beyond our control, no warranty, express or implied, is made and no liability is assumed by Pittsburgh Glass Works in connection with the use of this information.